



FLY-16SET

Order No.: 0259854

PRODUCTINFOS

16-channel wireless PA audio transmission set,

with UHF PLL technology.

- Consisting of 16-channel wireless PA audio transmitter FLY-16T and 16-channel wireless PA audio receiver FLY-16R
- For analogue wireless transmission of line audio signals in PA systems
- Frequency range: 823-832 MHz
- 16 pre-programmed channels, selectable
- Up to 8 intermodulation-free channels
- Audio transmission range: 30-17,000 Hz
- Compact size
- For further specifications, please refer to individual items

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

“An elegant solution for an irritating problem. Both time advantage and benefits for practical application are huge, especially when controlling the delay lines or for multi-room applications.”

delamar.de

“Simple transmission path for line signals. The FLY-16SET from IMG STAGELINE is a very compact, lightweight and easy-to-use wireless system for line signals which provides a perfect sound. The operation is licence-free in the EU. During our tests, the wireless connection has always been reliable and interference-free. The power is provided either via standard batteries AA size or via the supplied micro USB cable.”

SOUNDCHECK 02/2019

“Wireless system for audio line signals which is suitable for general applications. The signal quality absolutely meets professional requirements and can also be used for the transmission of master signals.”

OKEY 148

“Sometimes, it is the little things that make a musician's life a lot easier. During the test, the FLY-16 has really become one of our favourites. It is both practical and reliable [...] highly convenient systems. Even our active mobile phones did not interfere with the signal paths.”

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

TECHNICAL SPECIFICATIONS

FLY-16SET

General information

FLY-16SET

Description	16-channel wireless PA audio receiver
Carrier frequency range	823-832 MHz
Audio frequency range	30-17,000 Hz
Channels	1
THD	0.3%
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Transmitting power	10 mW
Operating range	approx. 90 m
Power supply transmitter	1 x 1.5 V batt. AA size, DC 5 V/150 mA via micro USB jack
Width transmitter	22 mm
Height transmitter	23 mm
Depth transmitter	116 mm
Weight transmitter	54 g
Connections transmitter	3-pole XLR jack
Specifications receiver	
Audio signal receiver	0.775 V (XLR, bal.)
Power supply receiver	1 x 1.5 V batt. AA size, DC 5 V/150 mA via micro USB jack
Width receiver	22 mm
Height receiver	23 mm
Depth receiver	102 mm
Weight receiver	25 g
Connections receiver	3-pole XLR plug

FLY-16SET

EAN code	4007754270044
Net weight	0.094 kg