



MMX-602/SW

Order No.: 0202230

PRODUCTINFOS

Microphone line mixer,

6 channels.

- 6 stereo line inputs, 6 balanced mono microphone inputs, switchable
- Adjustable automatic talkover (-12 dB), switchable for channel 1 or channels 1+2
- Balance control for each stereo input channel
- 3-way equalizer
- 12 V phantom power can be activated as required
- LED VU meter, peak LED
- Master output and record output
- Output can be switched stereo/mono
- Adjustable headphone output
- 482 mm (19") rack installation, 1 RU

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains

cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

MMX-602/SW

Input channels	6
Number of mix/mono	6
No. of stereo	6
Mic input	1 mV/6.6 kΩ, 6 x 3-pole XLR, bal.
Line input	100 mV/10 kΩ, 6 x RCA L/R
Master output	1 V/600 Ω, 1 x RCA L/R 1 x 3-pole XLR L/R, bal.
Record output	310 mV/600 Ω, 1 x RCA L/R
Headphones	> 8 Ω, 1 x 6.3 mm jack
Frequency range	20-20,000 Hz
THD	0.1%
S/N ratio	62 dB, unweighted
Equalizer bass	±12 dB/50 Hz
Equalizer midrange	±12 dB/1 kHz
Equalizer treble	±12 dB/10 kHz
Talkover	-12 dB, manual
Power supply	~ 230 V/50 Hz/12 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	12 VA
Admiss. ambient temp.	0-40 °C
Dimensions	482 x 47 x 208 mm, 1 RS
Width	482 mm
Height	47 mm
Depth	208 mm
Rack units, RU	1
Weight	2.8 kg
Packaging dimensions (W x H x L)	0.25 x 0.09 x 0.53 m

MMX-602/SW

Gross weight	3.76 kg
--------------	---------

Net weight	2.985 kg
------------	----------

MMX-602/SW

EAN code	4007754182736
----------	---------------

Net weight	2.985 kg
------------	----------