



## TXS-606HT/2

Order No.: 1000185

### PRODUCTINFOS

**Hand-held microphone with integrated multifrequency transmitter,**

with UHF PLL technology.

- Dynamic microphone cartridge, cardioid polar pattern
- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Adjustable sensitivity
- Switchable transmitting power (high: 25 mW/low: 2.5 mW)
- LCD for indicating group/channel, audio level and battery status
- Power supply via 2 x 1.5 V battery AA size (not supplied)

**There are restrictions or requirements within the EU!**

**Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**

### SOUNDCHECK 04/2012

"The TXS-646 can receive four wireless channels at the same time - the hand-held transmitter provides a

warm and powerful sound and stands its ground among the instruments ... the earband microphones allow for unobtrusive miking with both a low susceptibility to acoustic feedback and an excellent speech intelligibility ... the quad wireless system from IMG Stage Line provides a reliable operation at all times, is easy to use and impresses by a crisp sound."

+ Clear sound

+ Very good price-performance ratio

+ Future-proof frequency range

(Test setup consisted of TXA-646 with TXS-606HT, TXS-606LT and HSE-70A/SK)

### Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG

Konsul-Smidt-Str. 68

28217 Bremen

Germany

info@monacor.com

### Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

## TECHNICAL SPECIFICATIONS

### TXS-606HT/2

Description	hand-held microphone transmitter
Transmission method	wireless
Polar pattern	cardioid
System	dynamic
Carrier frequency range	672.000-691.975 MHz
Transmitting power	25 mW/2.5 mW
Power supply	2 x 1.5 V batt. AA size
Operating time	> 8 h
Audio frequency range	30-18,000 Hz
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 51 mm x 265 mm

**TXS-606HT/2**

Weight	312 g
Packaging dimensions (W x H x L)	0.075 x 0.06 x 0.295 m
Gross weight	0.461 kg
Net weight	0.323 kg

**TXS-606HT/2**

EAN code	4007754276183
Net weight	0.323 kg